Date	ORTHOMER ! CA®	CJsocket	TF TEST SOCKET BY MEASUR	EMENT
6333 North Orange	e Blossom Trail, Orlando FL 3281	0 • www.orthomerica.d	com • phone 877-737-8444 • fax 877-7	737-8445

		Remarks/Additional Prosthetic Components
Last Name / ID First Name Gender Male Female Age Height Shoe Size		
Diagnosis		
Practitioner	Phone/Fax	Shipping Company Service UPS Ground FedEx 2 Day Air Other: Overnight
Facility	PO Number	Need by
Ship to Address		Bill to Address
City De Acquisition Via: O Cast	State Zip t O Scan Affected Side:	City State Zip ○ Left ○ Right □ Cast Over Liner ○ 3mm ○ 6mm ○ 9mm
measure Email Orthome	erica a Picture of Pa	

150. 200mm. 250. mm ММ MM 300. mm 350. mm 400. mm. 450_

- ☐ Carving Only
- ☐ Test Socket Only
- ☐ Test Socket & Carving PETG or Orfitrans Stiff

Supply Lock


Y or N

- Dummy
 - ☐ Kiss
 - Bulldog
 - ☐ 4SN1
- None

- Attachment
 - 4 Hole Plate
 - □ 3 Prong (M or F)
- None

ORTHOMER**Î**C

CJSOCKET TF TEST SOCKET BY MEASUREMENT



Use ML stick applying sufficient pressure to simulate the desired socket ML dimension. All 4 measurements begin at the point where the proximal adductor longus will exit the socket.

1. Measured angularly to gluteus medius belly.

Measurements taken: Inches MM

- 2. Measured angularly to apex of GT.
- 3. Measured horizontal from proximal adductor longus to sub-trochanter.
- 4. Length of femur from the point where the proximal adductor longus will exit the socket.

Patient N	me / Purchase Order #:						
Patient Heigl	:, Patient Weight:, Amputated Side: Left Right						
Material C	lor: Coyote (brown) Heavy duty fabric (black only)						
Closure Options:							
] 1:1 Velcro attached to batten 2:1 Loops attached to batten 1" Pressure Buckles With Dacron Strap (No Velcro))					
Other Options:	Thumb Loop At End Of Strap 🔲 Dacron-backed Velcro Straps for 2:1 Loop Closure (HIH Straps	3)					
•	Proximal Arc (For very conical limbs or flexion contractures of 15 degrees or more)						
OPEN FLAP Design (No attachment holes medial side of Sail. Secured by selected closu							
	No attachment holes needed						
	Dart sewn into Sail (for irregular shaped limbs) Dart measurements: (H"xW")						
Special Instr	rtions:						

